



# JC400

## EdgeCam 2 4G Telematics DashCam



JC400 EdgeCam 2 can significantly increase the safety, efficiency, and sustainability of operations that power the fleet. Using the driver's behavior analysis of the driving recorder and G-sensor-induced collision technology. It helps you clarify what happens in case of an accident, resolve disputes related to road incidents and coach your drivers towards better driving.



### Various Communication Standards

It is able to communicate via 2G/3G/4G, WiFi, and Bluetooth.



### Dual Channel Recording

The integrated camera unit and the remote inward cabin-view camera can record the conditions of the road ahead and what happens inside the cab at the same time.



### Real-Time Tracking

The video recorder can be used as a tracker to locate the vehicle and collect and upload data such as speed and time in real-time.



### Event Video to Cloud

Videos triggered by a collision, vibrating, SOS call, and other exceptions will be auto uploaded to the cloud.



### Driving Behavior Analysis (DBA)

The dashcam can detect the driver's dangerous driving practices such as harsh acceleration, harsh braking, etc.



### Panic Button

This enables the driver to call for help in emergencies.

Logistics Vehicle



Ride-hailing



Dealership



# Specification

## Network

WiFi	2.4GHz, 802.11 b/g/n
BT	BLE 4.0
Eurasian Version	GSM: 850/900/1800/1900MHz WCDMA: B1/B2/B5/B8 FDD LTE: B1/B3/B5/B7/B8/B19/B20 TDD LTE: B38/B39/B40/B41 (100M)
American Version	GSM: 850/1800/1900MHz WCDMA: B2/B4/B5 FDD LTE: B2/B3/B4/B5/B7/B12/B17 TDD LTE: B38/B41 (100M)

## Configuration

CPU	Quad-core 1.4GHz A53
Operating System	Android 8.1 GO
GNSS	GPS+BDS
Sensor	6-axis
Mic	✓
Speaker	✓
Data Interface	Micro USB 2.0
Memory	TF card (Max. 256GB)
SIM Card	Nano
LED	Red (Power), Blue (Cellular), Green (GNSS)

## Camera

Main Unit	Front camera: 1920x1080/25FPS/F2.2/full color
Subcamera	Remote cabin-view camera: 1280x720/15FPS/F2.0/full color in daytime & monochrome in dim light
Image Format	H.264

## Others

Battery	External: 450mAh
Power Supply	Power cable: B+/ACC/GND
Operating Temperature	-20°C to +65°C
Operating Voltage	9-30V DC
Device Weight	233g
Device Dimension	109x69x52mm
Certifications	FCC/CE/RoHS